

Información Malla Electrosoldada Estándar

Medidas: Transversal 2.35mts - Longitudinal 6mts

Anterior Referencia	Nueva Referencia	No. de Grafiles		Separación (cm)		Diámetro (mm)		Peso (kg)
		Long	Trans	Long	Trans	Long	Trans	
M084	XX-084	16	40	15	15	4,0	4,0	18,81
M106	XX-106	16	40	15	15	4,5	4,5	23,75
M131	XX-131	16	40	15	15	5,0	5,0	29,26
M159	XX-159	16	40	15	15	5,5	5,5	35,53
M188	XX-188	16	40	15	15	6,0	6,0	42,18
M221	XX-221	16	40	15	15	6,5	6,5	49,40
M257	XX-257	16	40	15	15	7,0	7,0	57,38
M295	XX-295	16	40	15	15	7,5	7,5	65,93
M335	XX-335	16	40	15	15	8,0	8,0	75,05
M378	XX-378	16	40	15	15	8,5	8,5	84,55
H084	XY-084	16	24	15	25	4,0	4,0	15,09
H106	XY-106	16	24	15	25	4,5	4,0	17,58
H131	XY-1301	16	24	15	25	5,0	4,0	19,43
H158	XY-158	16	24	15	25	5,5	4,0	23,54
H221	XY-221	16	24	15	25	6,5	4,0	30,54
H257	XY-257	16	24	15	25	7,0	5,0	37,68
H283	XY-283	16	24	10	25	6,0	5,0	40,66
H335	XY-335	16	24	15	25	8,0	5,0	44,97
H378	XY-378	16	24	15	25	8,5	5,0	51,40
H442	XY-442	24	24	10	25	7,5	5,0	60,50
H503	XY-503	24	30	10	20	8,0	6,0	72,73
E050	XX-050	10	24	25	25	4,0	4,0	11,52

Su Mejor Opción en Mallas Electrosoldadas y Grafil

 **320 786 8790 - 665 9158**

Dirección: Calle 13 No 27A - 74 Acopi - Yumbo